




BELGAUM
aquavalves



Ball Valves – Trunnion Mounted–Three Piece Forged

Complies to BS EN ISO 17292(BS5351), API 6D

Sizes: 50 mm (2") to 750mm (30")

Type: Regular Bore & Full Bore

Rating: Class 150 to 2500

Materials: A105, LF2, F304 & F316

Seats: PTFE, Reinforced PTFE, Nylon, Metallic

Ends: Flanged & Weld

Specials: Fire safe test requirements of API607 & API 6FA

Ball Valves – Cryogenic Application

Complies to BS EN ISO 17292(BS5351), API 6D, BS 6364

Sizes: 15 mm (1/2") to 300mm (12")

Type: Regular Bore, Full Bore & Multi port

Rating: Class 150 to 600

Materials: LCB, CF8, CF8M, CF3, CF3M, CD4MCu etc

Seats: PTFE, Reinforced PTFE, Metallic

Ends: Flanged & Weld

Specials: Fire safe test requirements of API607 & API 6FA



Butterfly Valves – Bonded Seat Design

Complies to BS EN 593, API 609

Sizes: 40 mm (1 1/2") to 600mm (24")

Rating: PN10 & PN16

Materials: CI, DI, WCB, CF8, CF8M etc

Stem: 410, 304, 316 & 17-4PH

Ends: Wafer & Lugged

Soft seat: EPDM, NITRILE, NEOPRENE, SILICON & VITON

Double Flanged Butterfly Valves

Complies to BS EN 593

Sizes: 150 mm to 1200mm


Rating: PN6, PN10 & PN16

Materials: CI, DI, WCB, CF8, CF8M

Stem: 410, 304, 316, 17 4PH

Ends: Flanged

Soft seat: EPDM, NITRILE, NEOPRENE, SILICON & VITON



High Performance Butterfly Valves

Complies to API 609

Sizes: 80mm to 600mm

Rating: Class 150 & 300

Materials: WCB, CF8, CF8M

Stem: 410 & 17-4PH

Ends: Wafer & Lugged

Soft seat: PTFE, RPTFE, METAL

Specials: High Pressure, High Temperature